

December 2012

## ARAKS WOOD ADHESIVE

\*\*\*\*\*

In its kinds the installator ARAKS WOOD ADHESIVE is one of the best connector for wood industries, decoration with mirrors, furniture, paper, carton, etc.

### Technical Data:

|                       |                                                        |
|-----------------------|--------------------------------------------------------|
| <b>Base:</b>          | Poly Vinyl Acetate                                     |
| <b>Appearance:</b>    | Milky-white                                            |
| <b>Solid Content:</b> | 31%, minimum                                           |
| <b>Viscosity:</b>     | 500 to 1000 Poise (measured by Brookfield RV at 25 °C) |
| <b>pH Value:</b>      | 5 - 7                                                  |
| <b>Density:</b>       | 1.07gr/cm <sup>3</sup>                                 |

**Packing:** (gross weight)  
Pound (500 gr) , Quart (880 gr) , Buckets ( 3 Kg & 8 Kg) ,  
Plastic cans (10 Kg & 22.5 Kg) , Plastic vat( 60 Kg)  
and is supplied in two poly ethylene bags and then packed in 200 Kg rums.

### Instructions for Use:

- 1- Both sides of work place must be completely cleaned of dust, grease, etc.
- 2- Using painting brush apply a coat of wood adhesive to both surfaces.  
Press parts together immediately, wait for two hours.
- 3- It is required after using please close the door of can.
- 4 - Store in moderation .Do not use under +10 °C

### Shelf Life:

Approx .18 months indoor, in the temperature range of +5 °C – 40 °C