

December 2012

## DARKOOB WOOD ADHESIVE

\*\*\*\*\*

In its kinds the installator DARKOOB Wood Adhesive is a good connector for general purpose of cellulose industry, building industries ,paper, wood, cardboard.

### Technical Data:

|                       |   |
|-----------------------|---|
| <b>Base:</b>          | Poly Vinyl Acetate                                    |
| <b>Appearance:</b>    | Milky-white,  |
| <b>Solid Content:</b> | 36 %, minimum   |
| <b>Viscosity:</b>     | 450 to1200 Poise (measured by Brookfield RV at 25 °C) |
| <b>pH Value :</b>     | 5 - 7   |
| <b>Density:</b>       | 1.20gr/cm <sup>3</sup>                                |

### Packing:

(gross weight)  
Pound (500 gr), Quart (900 gr), Buckets (3 Kg & 8 Kg)  
Plastic cans (10 Kg & 22.5 Kg ) ,  
and is supplied in two poly ethylene bags and then packed in 200 Kg drums.

### Instructions for Use:

- 1-Only well dried and well conditioned pieces should be glued. The joints must be fitted exactly and be cleaned from dust, grease ,etc .spread the glue in a uniform film to one surface only in special cases to other parts .join the parts and press within the open time until sufficient strength has been attained.
- 2- Store in moderation.
- 3- Do not use under +10 °C.

### Shelf Life:

Approx .12 months indoor, in the temperature range of +5 °C – 40 °C